



DDL®

Durchführungstechnik
Dichtsysteme
Lutz

Tender specification text

Single-division building entry for buildings with basement

S-HEF single-division builder set for buildings with basement, for sealing pipes and cables against gas and water.

S-HEF single-division builder set for buildings with basement, for gas, water, power and telecommunication cables.

Type DD GF

for telecommunication (including corrugated tubes), glass fibre (fibre-optic)

S-HEF DD GF 12–16 / 2 x 7

double sealing (both sides of the wall), diameter 6 – 40 mm

double sealing (both sides of the wall), diameter 2 x 7 mm

- no concrete work
- no core-drilled holes
- no additional products (tubes, sleeves, hoses, seals)
- no assembly aids (torque wrench)
- quick and simple installation
- individually adaptable on site for cable and pipe diameters up to 40 mm
- standard tools (hammer drill, socket wrench, knife)
- subsequent upgrade to multiple-division penetration possible (horizontal and/or vertical arrangement)
- tight against gas and pressing water up to 1 bar (10 mWS)
- radon-resistant

Tests:

Tightness against gas and pressing water factory test DDL 07-1020

Radon safety IFA 200326-12

Tightness against gas and pressing water factory test MFPA P5.1/20488

Manufacturer:

DDL GmbH

Borsigstraße 26–28

D- 73249 Wernau

vertrieb@ddl-dichttechnik.de

www.ddl-dichttechnik.de



DDL®

Durchführungstechnik
Dichtsysteme
Lutz



DDL GmbH
Borsigstr. 26
73249 Wernau/N.

Tel. 07153 61093-0
Fax 07153 61093-029

vertrieb@ddl-dichttechnik.de
www.ddl-dichttechnik.de